

112.21



SHERWIN-WILLIAMS® C-70

**SHERWIN
WILLIAMS.**

SPACKLING AND PATCHING COMPOUND

PRODUCT DESCRIPTION

A heavy duty, professional grade spackling for smoothing larger cracks, holes and splits in drywall, plaster, wood, wallboard, brick, concrete and stucco. Its smooth consistency is easily applied with a putty knife or trowel and will not sag, crater or crack on normal applications. It will sand to a smooth, hard finish with minimal shrinkage.

- Professional grade
- Heavy duty formula
- Water clean-up
- Indoor/outdoor use

PRODUCT AVAILABILITY

Color	SMIS Number	Size
Antique White	151-2631	Quart
Antique White	151-2649	Gallon

Properties

Color:	Antique White
Tack-Free Time:	10 - 60 minutes
Cure Time:	30 - 60 minutes
Base:	Oil-water emulsion
Viscosity:	Mastic
Weight/Gallon:	12.9 - 13.2 lbs.
Weight Solids:	69.5 - 71.5%
Flammability:	Non-flammable
Odor:	Mild when wet, no odor when dry

112.21

SHERWIN-WILLIAMS® C-70

SPACKLING AND PATCHING COMPOUND



**SHERWIN
WILLIAMS.**

PREPARATION & USE

Surface must be clean and dry. It should be free from dirt, dust, grease, wax, and loose particles of paint. Roughen smooth surfaces with sand paper. For exterior use, countersink and prime all nail and screw heads.

APPLICATION:

Use at 50°F or above. Apply patching compound directly from the container using a putty knife or broad knife that is wider than the hole to be filled. Deep cracks or large holes should be filled in two applications. Smooth and allow to dry. After drying, sand to desired appearance.

PRIMING:

It is recommended to prime C-70 Compound prior to topcoating with paint. For best professional results and to prevent flashing, prime entire surface with a stain blocking primer prior to finishing coat. Spot priming or no priming at all can result in flashing or reverse flashing (shiners). The primer will aid in the uniformity of the top coat's appearance. Due to the porosity of some substrates, the entire surface to be painted may require primer for the most uniform appearance.

PAINTING: C-70 dries in 10 to 60 minutes and can be topcoated with most commonly used paint systems.

CLEAN UP: Clean up with water while still wet.

LIMITATIONS

INDOOR: Excessive heat near compound could promote a harmless odor. Compound must be dry before painting. If it is not dry, some color may bleed through on white or pastel colors. Not recommended for butt joints.

OUTDOOR: Use a stain blocking primer/sealer over all nail heads. Excess moisture in substrate will retard compound cure. If compound is not dry, staining could result. Skimming with compound can lead to loss of adhesion, cracking or paint alligating and is not recommended. Filling butt joints is also not recommended.

SHELF LIFE: Sherwin-Williams C-70 Spackling and Patching Compound will exhibit a 12 month shelf life from the date of manufacture when stored at room temperature.

PRECAUTIONS

Do not take internally. Keep out of the reach of children. Close container after each use. Protect from freezing. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer to other containers for storage.